



Scapa T001

High Performance Reverse Wound Transfer Tape

DESCRIPTION

Scapa T001 is a high performance reverse wound acrylic transfer tape with a high tack permanent adhesive onto a 92 gr. brown siliconised paper release liner with 0.04 mm total thickness. Recommended for all bonding, mounting and splicing applications.

APPLICATIONS

- Core starting of films, foils, paper webs.
- End tabbing of films, foils, papers.
- Mounting display items.
- Mounting promotional items.
- Mounting sample cards.
- Mounting albums, labels, leaflets, photo, posters, signs, stickers etc.
- Point of sale assembly.
- Show card assembly.

PRODUCT BENEFITS

- Excellent resistance to UV rays.
- Excellent temperature resistance.
- Long ageing performances.
- Reinforced with glass fibres for improved cohesive strength and clean break of adhesive.
- To be applied with **Scapa 9014 ATS** application gun for improved efficiency.
- Service temperature: -30°C to +150°C (withstands shorter periods up to 180°C).

TECHNICAL PROPERTIES

	Unit	Nominal value	Test Method
Total Thickness (without liner)	mm	0.040	AFERA 4006
Liner Thickness	mm	0.077	AFERA 4006
Adhesion to Steel	N/cm	2.6	AFERA 4001

STANDARD PRESENTATION

- Roll length: 33 metres
- Roll width: 12 and 19 mm
- Core: 25.4 mm plain plastic core
- Packaging: Flow Pack
- Colour: Clear

RECOMMENDATIONS

The rolls should be stored in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C.

Under these conditions, we recommend to use the product within 12 months from the date of manufacture.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.