



## 1522 DOUBLE COATED MEDICAL TAPE

**MATERIAL DESCRIPTION:** Double coated medical tape consisting of a 3 mil transparent polyethylene film, coated on both sides with a hypoallergenic, pressure sensitive acrylate adhesive. The tape is supplied on a bleached Kraft-Glassine paper liner, with a basis weight of 80 pounds; silicone coated both sides, which has a nominal caliper of 4.5 mils (0.11 mm). The tape is wound with the liner on the outside of the roll.

### ROLL DIMENSIONS:

Length:	Maximum 400 yd (366 m) $\pm$ 2%
Width:	Maximum 48 in (122 cm) $\pm$ 1/32 in (1.0 mm)
Note:	Tape supplied on 3-inch (76 mm) cores

**SPLICES:** Splices on the tape and liner are intended for continuous processing.

<u>Roll Width</u>	<u>Maximum Splices Per Roll</u>
$\leq$ 8 in (20 cm)	2 per 100 yd (91 m)
	3 per 200 yd (183 m)
	6 per 400 yd (366 m)

Information on the splice frequency in roll widths greater than 8 in (20 cm) is available upon request.

### PRODUCT PROPERTIES:

Adhesion to steel:	Minimum 400 g/25 mm (14 oz/in) (3.92 N/25 mm)
Liner release:	Maximum 30 g (0.29 N)/25 mm
Tape caliper w/o liner:	6.3 mils $\pm$ 1.0 mil (0.16 mm $\pm$ 0.025 mm)

Product as supplied in original packaging, will maintain stated test properties for a period of three years from date stamped on shipping container, when stored at a temperature between 50-80°F (10-27°C) and a relative humidity between 40 and 60 percent.

*Specialist converters of technical adhesive tapes and foams*

Tape Range Distributors Limited  
Captain Clarke Road, Broadway Industrial Estate, Hyde, Cheshire, SK14 4QG.  
Tel: +44 (0)161 351 9515 Fax: +44 (0)161 351 9516  
email: [taperange@adhesivetape.net](mailto:taperange@adhesivetape.net)  
vat no: 509 5005 65 reg no: 2578452

