



## 3120 High Performance Modified Acrylic Reinforced Tape 80gsm Amber Release Liner

<u>TECHNICAL DETAILS</u>	<u>TYPICAL VALUE</u>	<u>UNITS</u>
Thickness, adhesive + carrier	0.1	mm
Adhesive coat weight	80-90	Gsm
Release liner thickness	0.07	Mm
180 Degree peel adhesion to steel	1000	N/m
Loop Tack	1200	N/m
Liner Release	10	N/m
Service temperature	-20 to +120	Deg.C
Recommended application temp.	+5 to +25	Dec.C
Moisture vapour permeability	Less than 1	g/m2, 24h at 40deg.C, 90% RH
Shear adhesion, 1KG @ 23 deg.C	20	Hours
Shelf life	12	Months

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND FOR GUIDANCE ONLY.  
ALL DATA IS BASED UPON AVERAGE VALUES. THE PURCHASER SHALL BE RESPONSIBLE FOR DETERMINING THE SUITABILITY OF THIS PRODUCT FOR THEIR PURPOSES.

*Specialist converters of technical adhesive tapes and foams*

Tape Range Distributors Limited  
Captain Clarke Road, Broadway Industrial Estate, Hyde, Cheshire, SK14 4QG.  
Tel: +44 (0)161 351 9515 Fax: +44 (0)161 351 9516  
email: [taperange@adhesivetape.net](mailto:taperange@adhesivetape.net)  
vat no: 509 5005 65 reg no: 2578452

