



DF-2501

Description

Black Closed-Cell Double Sided Polyethylene Foam Tape, with solvent-based acrylic adhesive and green polyethylene liner.

Applications

Particularly suitable for automotive applications, such as badge/emblem fixing. Also suitable for use with mirrors, display stands and hangers, etc. For use indoor and outdoor.

Features

High tack adhesion properties.

Excellent resistance to solvents, plasticizers, grease, humidity and UV

Good resistance to temperatures

	Unit of Measurement	Value
Total Thickness	mm	0.9
Adhesion to steel	N / 25mm	>15
Cohesion	mins	480
Temperature Resistance	°C	+70
Tack	cm	< 8

All products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

All information is subject to change without prior notice.

Specialist converters of technical adhesive tapes and foams

Tape Range Distributors Limited
Captain Clarke Road, Broadway Industrial Estate, Hyde, Cheshire, SK14 4QG.
Tel: +44 (0)161 351 9515 Fax: +44 (0)161 351 9516
email: taperange@adhesivetape.net
vat no: 509 5005 65 reg no: 2578452

